

Gene Expression Analysis Use of Bioconductor and *limma*





Today's Outline

- Part A : Introduction of probabilistic models Bayesian Inference Probabilistic models for gene expression data microarray data: Gene Expression Estimation with *puma*
- Break (questions if any)
- Part B : Probabilistic models for gene expression data Differential Expression Analysis False Discovery rate

Bioconductor and limma





Today we will be learning:

- What are probabilistic models and how they work on high throughput data
- Bayes' Rule
- Uncertainty in probabilistic models
- *puma:* probabilistic model for gene expression data
- Differential Expression Analysis for gene expression data
- The concept of False Discovery Rate applied to gene expression data
- Bioconductor : Open Source Platform for gene expression data
- *limma* package



Probabilistic Models

A *probability model* is a mathematical representation of a random phenomenon. It is defined by its sample space, events within the sample space, and probabilities associated with each event.

These are models that represents unknowns in terms of probability distributions instead of values and a confidence interval.

For example if we assume that the data is generated by:

 $\theta \sim N(\mu | \sigma)$



we can measure few samples of it, but we don't know the true distribution:

$$\theta \sim \mathbf{S} = \{s_1, \ldots, s_n\}$$



BMS353



Probabilistic Models (cont.)

We can use a probability theory to manipulate those functions (probabilities) and make inference on the unknown parameters as well as evaluate the *uncertainty* that is associated to their estimates. In other words:

- We describes data that one could observe from a system
- We use the mathematics of probability theory to express all forms of uncertainty and noise associated with our model...
- We use inverse probability (i.e. Bayes rule) to infer unknown quantities, adapt our models, make predictions and **learn** from data.

Why are they good?

- They Faithfully represent uncertainty in our model structure and parameters and noise in our data
- They are automated, adaptive and robust
- They scale well to large data sets



Bayes' Rule

 $P(hypothesis | data) = \frac{P(data | hypothesis)P(hypothesis)}{P(data)}$

 Bayes rule tells us how to do predict outcomes of hypotheses from data. We can do inference about hypotheses once we have observed the data



Rev'd Thomas Bayes (1702-1761)

• Learning and prediction can be seen as forms of inference. If we use Bayes' Rule we call it *Bayesian Inference*

P(hypothesis) = prior P(hypothesis|data) = posterior P(data|hypothesis) = likelihood P(data) = marginal likelihood

Not always possible to be computational efficient and likelihood are estimated using sampling methods.

BMS353



Uncertainty in Biology

In biology the complexity of the systems is such that we cannot measure everything and predictions of data required an additional "knowledge" to become meaningful.

This "knowledge" needs to be quantified in a way that reflects our prior knowledge of the systems and what we were able to measure (observe) and adjusted once the measurements are computed. It opens the way to quantifying uncertainty.

The evolution of the technology for biological sciences enables us to apply the concepts of uncertainty on complex biological data.

When we cannot quantify the parameters that are needed to describe the system we have to include the uncertainty associated to this "unknown" in our model.

We use probabilistic models to build machines (models implemented in an algorithm) that *learn* from the data. This filed of research is called **Machine Learning**.





How do probabilistic model help in gene expression analysis?

We know that:

- 1. Summarise to a single expression level the probe intensities for each probe set
- 2. Estimate the variations introduced by background effect probe affinity effect
- 3. Some PM/MM pairs are more reliable than others



4. The signal needs to be scaled before comparing data from different arrays

They can help to define a measure that best represent the absolute expression level of each gene on the chip?





The approaches

Use Statistical Approach

make use of the information we have to define values that estimate gene expression

MAS 5.0 RMA

Use a probabilistic approach

make use of the observed data to estimate probability functions that have generated that data

built a noise model and evaluate the uncertainty in the system

Estimates of gene expression will be the most probable value that summarises the observed values.



puma Propagating Uncertainty in Microarray Analysis



Estimate the distribution of the data and we learn the parameters to define it from the data (gamma distributions)

We built priors on the hypothesis (our belief is that the true signal is gamma distributed

We then calculate the likelihood using the model defined by Affymetrix

Signal= PM-MM

We apply Bayes' rule to calculate the signal distribution (posterior)



The advantage of using uncertainty

Robust gene expression estimates depend on how well we are able to quantify the uncertainty.

Down stream analysis will be more effective and number of false positives will be reduced.

Probability of Positive Log Ratio | one sided Bayesian test in which we use also the variances



The advantage of using uncertainty (cont.)

Improves accuracy in High level Analysis:

- DE Analysis using a ranking based on Probabilities of Positive Log Ratio

 Ranking defining False Discovery Rate (FDR) and q-values using PPLR
- Principal component analysis (*pumaPCA*)
- Clustering methods with mixture components (*pumaClust*)
- Linking SNPs and gene expression to identify functional effects. (*NG*)
- Gene networks we are working on this.





Part B





High Level Analysis: workflow example

- 1. Visualisation of the data
- 2. *High level summary*: Combine expression from replicated arrays
 - Combine expression and uncertainty (puma)
 - Combine information from replicates with single point statistics
- 3. Differential Expression Analysis: Determine differential expression between conditions, or between more complex contrasts such as interaction terms
- 4. Dimensionality reduction Principal Component Analysis (Week 11)
- 5. Data Clustering: Cluster data taking the expression-level uncertainty into account (week 11)



Differential expression Analysis

GOAL:

Identify the most differentially expressed genes across different conditions or cases and controls.

HOW:

identify a threshold that "define" differential expression FC values p-values

What happens if the sample size is small?

- The fold-change becomes very sensitive to outliers
- The t-test becomes very sensitive to small variances





The Fold Change

Given two gene expression values **x** and **y** the fold change is defined as

 $FC = \frac{x}{y}$

Given two vectors \mathbf{x}_j and \mathbf{y}_j of gene expression measurements for controls and cases for GENE j, the fold change is defined as

$$FC_j = \frac{x_j}{y_j}$$

It can also appear as a difference when we use the log transformation of the data.

Problem: How do we manage replicates? We need to combine the data



High Level summary

High level summary: Combine expression from replicated arrays

This is prior our DE and it is useful to have a representative gene expression value for the class you are studying : Wild Type vs Mutant; Disease vs Control.

- Combine information from replicates with single point statistics
- Combine expression and uncertainty (puma) using Bayesian Inference

In both cases you need a measure of uncertainty.

How do we get it in both cases?

Differential Expression: pumaDE and PPLR



Example:

The University

Of Sheffield.

In differential Expression analysis the goal is to estimate genes that change across conditions.

What happens then if we do not evaluate uncertainty?

Probability of Positive Log ratio: PPLR

Gives the probability of the log ratio (log FC) to be positive.





Data from Choe et al, Genome Biology(2005)



The problem of Multiple sampling

small number of replicates due to the high cost of data generation, and the need for a very large number of significance tests.



how can we determine an appropriate significance level? Methods to correct the significance level are called multiple tests corrections (or multiple comparisons corrections)



Multiple testing

The **Bonferroni correction** is a classical correction method the significance level to be used for each of 10 000 tests is $0.05/10\ 000 = 5 \times 10-6$.

A fundamental principle of statistical analysis is that fewer false positives are associated with more false negatives (type II errors), that is, a higher chance of missing truly differentially expressed genes.

We need a more relaxed method than the Bonferroni correction.

However, one common problem associated with the classical type of multiple tests correction is that it is difficult to estimate the number of fase positive in order to choose the decision threshold

Use no correction for multiple hypotheses is too optimistic

Bonferroni's correction: too pessimistic...



False Discovery Rate

An alternative is the false discovery rate (FDR). FDR = number of false positive features/ number of significant features

false discovery rate (FDR) has become a standard for multiple tests correction in microarray data analysis.

The idea of FDR put forward by Benjamini and Hochberg (Benjamini & Hochberg, 1995) is that it would be convenient to know what per cent of the positives discovered by multiple significance tests are false positives

NOTE: FDR depends on the distribution of p-values and not on the number of tests.



Then What do we do in practice?

LIMMA: propose a moderated t-statistic Smyth, G. K. (2004). Linear models and empirical Bayes methods for assessing differential expression in microarray experiments. Statistical Applications in Genetics and Molecular Biology 3, No. 1,

PPLR –*puma:* This model takes into account both the technical and the biological variance and significance of differential expression can then be evaluated by calculating probabilities.

$$FDR(1..n) = \frac{1}{n} \sum_{i=1}^{n} 1 - PPLR(i)$$



False Discovery Rate



when a significance level of 0.03 is used, the FDR = 300/756 = 0.40. Now we know that on average 40% of 756 genes are false positives

if we use a significance level of 0.01 (green line), the number of true positives is 380, and the number of false positives is 100, so the FDR = 0.21

At a significance level of 0.0007321 the FDR = 0.05, which corresponds to (on average) 141.5 true positives and 7.5 false positives – with Bonferroni an average of 3 true positives and no false positives.



Bioconductor

~				Search:		
Bioconductor	Home	Install	Help	Developers	About	

About Bioconductor

Bioconductor provides tools for the analysis and comprehension of highthroughput genomic data. Bioconductor uses the R statistical programming language, and is open source and open development. It has two releases each year, <u>1104</u> <u>software packages</u>, and an active user community. Bioconductor is also available as an <u>AMI</u> (Amazon Machine Image) and a series of <u>Docker</u> images.

News

- Bioconductor <u>3.2</u> is available.
- Bioconductor <u>F1000 Research Channel</u> launched.
- Orchestrating high-throughput genomic analysis with *Bioconductor* (<u>abstract</u>) and other <u>recent literature</u>.
- Read our latest <u>newsletter</u> and <u>course</u> <u>material</u>.
- Use the <u>support site</u> to get help installing, learning and using Bioconductor.







Bioconductor (cont.)

- Bioconductor is an open source and open development software project, many packages are added and updated very frequently.
- Some of them are 'personal selection' based on what is my experience in teaching and research.
- To obtain a broad overview of available Bioconductor packages, it is strongly recommended to consult its official project site and remember always to check on updates.
- It is absolutely critical to use the original documentation of each package (PDF manual or vignette) as primary source of documentation.



Bioconductor (cont.)

Affy Packages

These are the key packages for the analysis of affymetrix microarray data.

Affy

The Affy package provides the basic single point statistics methods for analysing affymetrix oligonucleotide arrays

Obtaining log transformed expression values with 3 different methods (MAS5, RMA, GCRMA)

Puma Packages

These are the packages for the analysis of affymetrix microarray data with probabilistic methods.

The gene expression levels are stored in what is called *Expression set* and the experimental design in what is called *Pheno Data*





Differential Expression: limma

Visualization and quality controls

We will use hist(), boxplot() and mva.plot() and the *limma* version to visualise the data from the expression sets.

Analysis of Differentially Expressed Genes

Limma

Limma is a software package for the analysis of gene expression microarray data, that make use of linear models for analysing *designed experiments* and the assessment of differential expression.

The differential expression methods apply to all array platforms and treat Affymetrix, single channel and two channel experiments in a unified way.

Refer to the *limma* manual for examples and methods.



Limma requires two matrices are specified:

- the design matrix which provides a representation of the different RNA targets which have been hybridized to the arrays.
- the contrast matrix which defined the combination of comparisons (*contrasts*). For very simple experiments the contrast matrix may not need to be specified explicitly.

> design

Dil N	The second	0		
FlieName	Target		T	MIL
File1	WT	w	T	MUVSWI
Filo2	WT	Array1	1	0
File2	VV I	Array2	1	0
File3	Mu	Arrav3	1	1
File4	Mu	Arrav4	1	1
Filos	Mn			-
гпер	IVIU	Array5	1	1



How do we use limma?

Fist step : define the matrices

Second step:

Fit a linear model to explain the relation between each gene on the array and the design matrix

$$E(y_i) = X\alpha_i$$

Where y_i is the gene expression for gene i, X is the design matrix and α_i is the coefficient for the gene i

Third Step: define significance levels for the comparisons. We use an empirical Bayes t-test, to calculate the p-values. This is to ensure that the information is learned from the data as a whole rather than single point.

Fourth Step: Select the significant targets and visualise the data





We have seen today how to estimate gene expression

single point statistics probabilistic models Uncertainty and how we can use it

Differential Expression Analysis

p-values and their problems with gene expression data False Discovery Rate

Bioconductor Project

limma for Differential Expression